

# H Series HA-3016A

## 16 Band Handheld 3G、4G with Wi-Fi、5G、Remote、GPS Jammer

NEW Next Generation digital cell phone jammer top of the range; a mobile device to help circumvent disturbances or noise from cellular phone calls - the latest high-power hand-held cell phone and Wi-Fi jammer with an internal, high-capacity battery, universally compatible with new (LTE, Wi-Max) 4G / 3G / 2G / Wi-Fi / 5G/GPS networks. Selectable dip switches on the side for choice of jamming bands or save battery power.

### Specifications

HA-3016-E(Europe) 5G + 5GHZ	HA-3016-A (America) 5G + 5GHz
758-830MHz: 1.0W 5G, 4G LTE Low	850-895MHz: 1.0W CDMA 850
920-965MHz: 1.0W GSM900	1800-2000MHz: 1.0W DCS, PCS
1800-1920MHz: 1.0W DCS	2100-2170MHz: 1.0W 3G, UMTS
2100-2170MHz: 1.0W 3G, UMTS	2300-2500MHz: 1.0W 4G LTE + WiFi 11.b & g
2400-2500MHz: 1.0W WiFi 11.b & g	2500-2700MHz: 1.0W 4G WiMAX Sprint
2570-2690MHz: 1.0W 4G LTE High	700-800MHz: 1.0W 4G LTE USA iPhone (AT&T & Verizon)
1450-1620MHz 1.0W 5G+ GPS L1 +Glonass L1	1570-1620 MHz: 1.0W GPS L1 + Glonass L1
164-173MHz :1.0W Lojack 164MHz	173MHz 1.0W
315MHz :1.0W Remote Control	315MHz :1.0W Remote Control
433MHz :1.0W UHF Remote Control	433MHz :1.0W UHF Remote Control
868MHz: 1.0W Remote Control	868MHz: 1.0W Remote Control
5.1-.5.9GHz :1.0W WiFi 11.a	5.1-.5.9GHz :1.0W WiFi 11.a
1170-1280MHz: 1.0W GPS L2 + L5+ Glonass L2	1170-1280MHz: 1.0W GPS L2 + L5+ Glonass L2
5G 3400-3600MHz 1.0W 5G LTE	5G 617-652MHz 1.0W 5G LTE
5G 3600-3800MHz 1.0W 5G LTE	1700-1800MHz : 4G LTE
400-480MHz :1.0W UHF Remote Control	400-480MHz :1.0W UHF Remote Control
<b>Total: 16.0 W</b>	<b>Total: 16.0 W</b>

All Frequency can mix very flexible; each module/Band is independent.

Using Omni directional dipole antenna, gain value 2 ~ 3dBi.

- Each band can operate independently with DIP switch ON / OFF.
- Band power output per LED indicato.
- Battery: Ni-MH battery 16000mHA can support 3Hrs of continuous working.
- Good heat dissipation, lower then 40°C when continuous operating.
- Built-in battery charger, you can charge while using support.
- Cover range: 10 ~ 30 M radius around the signal strength required for -80dBm based.
- Input voltage: AC 110-240V / 50-60Hz or DC 12.
- Support car charger.
- Weight: about 1.8kg
- Size: 200 \* 135 \* 50 mm.
- Warranty time: One year.

Option portable packing case  
Size: 335 x 260 x 130mm, 1.2kg

